Culp, Inc.



Flammability Passes:

California Tech. Bulletin #117-2013 UFAC Class 1 NFPA 260 Class 1

content:	79% Polyester, 21% Rayon
backing:	100% Polyester non-woven scrim
finish:	i-clean – a high performance stain moisture repellent, based on Nano technology.
Repeat: weight: width:	N/A 9.0 oz. / lin. yd. 54 inches

Specifications:

Performance:			
abrasion:	Heavy Duty – 75,000 cycles		
	(Wyzenbeek – Cotton duck Abradant) (ASTM D4157)		
light fastness:	Class 4/40 hrs. min. (AATCC16A)		
color fastness:	Class 3 (ASTM D3597, AATCC 8) Wet		
	Class 4 (ASTM D3597, AATCC 8) Dry		
physical properties:	Class 3 (ASTM D3511) Brush Pill		
	152 lbs. warp, 116 lbs. weft (ASTM D5034) Breaking Strength		
	52 lbs. warp, 55 lbs. weft (ASTM D4034) Seam Slippage		

made in:

China

Care & Cleanability:

Cleaning code **W** - Spot clean only with water-based upholstery shampoo or foam upholstery cleaner. Pretest a small, inconspicuous area before proceeding. Do not over wet. Do not use solvents to spot clean. Cushion covers should not be removed and laundered. When cleaning a spill, blot immediately to remove the spilled material. Evenly clean the entire panel in a seam to seam fashion. Do not clean just the spots or stains. When an overall soiled condition has been reached and professional care is required, contact an IICRC certified firm (www.iicrc.org).