Culp, Inc.

ARVIS



Specifications:

content:	100% Polyester
base cloth:	Cindy
finish:	i Clean
Repeat:	18" W x 18" H
weight:	7.2 oz. / lin. yd.
width:	54 inches

Flammability Passes:

California Tech. Bulletin #117-2013
UFAC Class 1
NFPA 701 Method 1

Performance:

abrasion:	Heavy Duty – 60,000 cycles
	(Wyzenbeek – Cotton duck Abradant) (ASTM D4157)
light fastness:	Class 4/40 hrs. min. (AATCC16A)
color fastness:	Class 3 (ASTM D3597, AATCC 8) Wet
	Class 4 (ASTM D3597, AATCC 8) Dry
physical properties:	Class 3 (ASTM D3511) Brush Pill
	65 lbs. warp, 68 lbs. weft (ASTM D5034) Breaking Strength
	40 lbs. warp, 44 lbs. weft (ASTM D4034) Seam Slippage
recommended use:	Bedding, Drapery, Upholstery
made in:	China

Care & Cleanability:

Cleaning code **W** - Spot clean only with water-based upholstery shampoo or foam upholstery cleaner. Pretest a small, inconspicuous area before proceeding. Do not over wet. Do not use solvents to spot clean. Cushion covers should not be removed and laundered. When cleaning a spill, blot immediately to remove the spilled material. Evenly clean the entire panel in a seam to seam fashion. Do not clean just the spots or stains. When an overall soiled condition has been reached and professional care is required, contact an IICRC certified firm (www.iicrc.org).