

EQUIS



Specifications:

content: 100% Polyurethane
 backing: 100% Polyester
 finish: iClean
 Repeat: n/a
 weight: 18 oz. / lin. yd.
 width: 54 inches

Flammability Passes:

California Tech. Bulletin #117-2013
 UFAC Class 1
 NFPA 260 Class 1

Performance:

abrasion: Heavy Duty – Exceeds 100,000 cycles
 (Wyzenbeek – Cotton duck abradant) (ASTM D4157)
 light fastness: Class 4/200 hrs. min. (AATCC16A)
 color fastness: Class 4 (ASTM D3597, AATCC 8) Wet
 Class 4 (ASTM D3597, AATCC 8) Dry
 physical properties: 81 lbs. warp, 165 lbs. weft (ASTM D5034) Breaking Strength
 61 lbs. warp, 63 lbs. weft (ASTM D4034) Seam Slippage
 recommended use: Upholstery
 made in: China

Care & Cleanability:

Cleaning code **W** – Spot clean with water based upholstery shampoo or foam upholstery cleaner. Pretest a small, inconspicuous area before proceeding. Do not over wet. Do not use solvents to spot clean. Cushion covers should not be removed and laundered. When cleaning a spill, blot immediately to remove the spilled material. Evenly clean the entire panel in a seam to seam fashion. Do not clean just the spots or stains. When an overall soiled condition has been reached and professional care is required, contact an IICRC certified firm (www.iicrc.org.)