

HERRING



Specifications:

content: 100% Polyester
 backing: Synthetic Latex Blend
 finish: iClean
 repeat: 7.09" W x 7.99" H
 weight: 18.08 oz. / lin. yd.
 width: 54 inches

Flammability Passes:

California Tech. Bulletin #117-2013
 UFAC Class 1
 NFPA 260 Class 1

Performance:

abrasion: Heavy Duty – 100,000 cycles
 (Wyzenbeek – Cotton duck Abradant) (ASTM D4157)
 light fastness: Class 4/40 hrs. min. (AATCC16A)
 color fastness: Class 4 (ASTM D3597, AATCC 8) Wet
 Class 4 (ASTM D3597, AATCC 8) Dry
 physical properties: Class 4 (ASTM D3511) Brush Pill
 262 lbs. warp, 305 lbs. weft (ASTM D5034) Breaking Strength
 59 lbs. warp, 47 lbs. weft (ASTM D4034) Seam Slippage
 made in: China

Care & Cleanability:

Cleaning code **W** - Spot clean only with water based upholstery shampoo or foam upholstery cleaner. Pretest a small, inconspicuous area before proceeding. Do not over wet. Do not use solvents to spot clean. Cushion covers should not be removed and laundered. When cleaning a spill, blot immediately to remove the spilled material. Evenly clean the entire panel in a seam to seam fashion. Do not clean just the spots or stains. When an overall soiled condition has been reached and professional care is required, contact an IICRC certified firm (www.iicrc.org).