



Specifications:

content: 100% Polyester

backing: Synthetic latex blend

finish: iClean

repeat: 14.41" H x 8.07" W

weight: 12.17 oz. / lin. yd.

  

width: 54 inches

Flammability Passes:

California Tech. Bulletin #117-2013  
 UFAC Class 1  
 NFPA 260 Class 1

Performance:

abrasion: Heavy Duty – 100,000 cycles  
 (Wyzenbeek – Cotton duck Abradant) (ASTM D4157)

light fastness: Class 4/40 hrs. min. (AATCC16A)

color fastness: Class 4 (ASTM D3597, AATCC 8) Wet  
 Class 4.5 (ASTM D3597, AATCC 8) Dry

physical properties: Class 4 (ASTM D3511) Brush Pill  
 237 lbs. warp, 189 lbs. weft (ASTM D5034) Breaking Strength  
 63 lbs. warp, 53 lbs. weft (ASTM D4034) Seam Slippage

made in: China

Care & Cleanability:

Cleaning code **W** - Spot clean only with water based upholstery shampoo or foam upholstery cleaner. Pretest a small, inconspicuous area before proceeding. Do not over wet. Do not use solvents to spot clean. Cushion covers should not be removed and laundered. When cleaning a spill, blot immediately to remove the spilled material. Evenly clean the entire panel in a seam to seam fashion. Do not clean just the spots or stains. When an overall soiled condition has been reached and professional care is required, contact an IICRC certified firm ([www.iicrc.org](http://www.iicrc.org)).