Culp, Inc.



Flammability Passes:

California Tech. Bulletin #117-2013 UFAC Class 1 NFPA 260 Class 1

Specifications:

content:	80% Polyester, 20% Acrylic
backing:	Synthetic latex blend
finish:	i-clean, a high-performance stain repellant based on Nano technology
Repeat:	N/A
weight:	24.4 oz./lin. yd.
width:	54 inches

ASTM E84

Performance:			
	abrasion:	Heavy Duty – 100,000 cycles	
		(Wyzenbeek – Cotton duck Abradant) (ASTM D4157)	
	light fastness:	Class 4/40 hrs. min. (AATCC16A)	
	color fastness:	Class 3 (ASTM D3597, AATCC 8) Wet	
		Class 4 (ASTM D3597, AATCC 8) Dry	
	physical properties:	Class 3 (ASTM D3511) Brush Pill	
		229 lbs. warp, 188 lbs. weft (ASTM D5034) Breaking Strength	
		33 lbs. warp, 54 lbs. weft (ASTM D4034) Seam Slippage	

made in:

China

Care & Cleanability:

Cleaning code **W** - Spot clean only with water-based upholstery shampoo or foam upholstery cleaner. Pretest a small, inconspicuous area before proceeding. Do not over wet. Do not use solvents to spot clean. Cushion covers should not be removed and laundered. When cleaning a spill, blot immediately to remove the spilled material. Evenly clean the entire panel in a seam to seam fashion. Do not clean just the spots or stains. When an overall soiled condition has been reached and professional care is required, contact an IICRC certified firm (www.iicrc.org).